



EN 1504-4

08

0921

VYHLÁSENIE O PARAMETROCH

Sikadur®-31 CF Normal

02	04	02	03	001	0	000039	1001
----	----	----	----	-----	---	--------	------

1. Typ výrobku:

Jedinečný identifikačný kód typu výrobku:

Sikadur®

2. Typ, číslo výrobnej dávky alebo sériové číslo, alebo akýkoľvek iný prvok umožňujúci identifikáciu stavebného výrobku, ako sa vyžaduje podľa článku 11 ods. 4:

-31 CF Normal

(číslo šarže – vid' údaj na balení)

3. Zamýšľané použitia alebo použitia stavebného výrobku, ktoré uvádza výrobca, v súlade s uplatniteľnou harmonizovanou technickou špecifikáciou:

Výrobok na konštrukčné lepenie

Metóda opravy (4.4)

Podľa prílohy ZA tabuľky ZA.1b

4. Meno, registrované obchodné meno alebo registrovaná ochranná známka a kontaktná adresa výrobcu, ako sa vyžaduje podľa článku 11 ods. 5:

Sikadur®

Sika Schweiz AG
Tüffenwies 16
CH-8048 Zürich
Švajčiarsko

5. Kontaktná adresa:

V prípade potreby meno a kontaktná adresa splnomocneného zástupcu, ktorého splnomocnenie zahŕňa úlohy vymedzené v článku 12 ods. 2:

Nie je relevantné (vid' článok 4)

6. Systém alebo systémy posudzovania a overovania nemennosti parametrov stavebného výrobku, ako sa uvádzajú v prílohe V:

Systém 2+ (pre použitie na budovy a stavby v pozemnom stavitelstve)

Systém 3 (pre použitie podľa reakcie na oheň)

7. Notifikovaná osoba (hEN):

V prípade vyhlásenia o parametroch týkajúceho sa stavebného výrobku, na ktorý sa vzťahuje harmonizovaná norma:

EN 1504-4, Systém 2+:

Notifikovaná osoba č. 0921 vykonala počiatočnú inšpekciu výrobného závodu a systému riadenia výroby a vykonáva priebežný dohľad nad systémom riadenia výroby a posudzovanie a hodnotenie systému riadenia výroby. Notifikovaná osoba vydala certifikát o zhode systému riadenia výroby č. 0921-CPR-2054

EN 1504-4, Systém 3:

Notifikovaná osoba MPA Drážďany, č. 0767
 vykonala skúšku reakcie na oheň podľa systému
 3 a vydala protokol o skúške **2007-B-4394/08**
 a protokol o klasifikácii **2007-B-4394/07**.

8. Notifikovaná osoba (ETA):

V prípade vyhlásenia o parametroch týkajúceho
 sa stavebného výrobku, na ktorý bolo
 vypracované európske technické posúdenie:

Nie je relevantné (viď článok 7)

9. Deklarované parametre

Výrobok na konštrukčné lepenie reprofilačnou maltou alebo betónom na iné zamýšľané použitie, ako je použitie s nízkymi funkčnými požiadavkami			
Podstatné vlastnosti	Parametre	Skúšobná metóda	Harmonizovaná technická špecifikácia
Prídržnosť/ priľnavosť:	vyhovuje (zlom betónu)	EN 12636	EN 1504-4:2004
Pevnosť v šmyku:	$\geq 6 \text{ N/mm}^2$	EN 12615	
Pevnosť v tlaku:	$\geq 30 \text{ N/mm}^2$	EN 12190	
Zmraštenie/ rozťažnosť:	$\leq 0,1\%$	EN 12617	
Spracovateľnosť:	60 min. pri 20°C	EN ISO 9514	
Citlivosť na vodu:	vyhovuje	EN 12615	
Modul pružnosti:	$\geq 2000 \text{ N/mm}^2$	EN ISO 178	
Koeficient teplotnej rozťažnosti:	$\leq 100 \cdot 10^{-6}$	EN 1770	
Teplota sklovitého prechodu:	$\geq 40^\circ\text{C}$	EN 12614	
Reakcia na oheň:	Eurotrieda E	EN 13501-1	
Trvanlivosť:	vyhovuje	EN 13733	
Nebezpečné látky:	NPD	(spĺňa 5.4)	

NPD – Parameter neurčený

10. Deklarácia

Parametre výrobku uvedené v bodoch 1 a 2 sú v zhode s deklarovými parametrami v bode 9.

Toto vyhlásenie o parametroch sa vydáva na výhradnú zodpovednosť výrobcu uvedeného v bode 4.

Podpísal(-a) za a v mene výrobcu:

nečitateľný podpis
 Rahel Nägeli Ganz
 Product Engineer

nečitateľný podpis
 Roland Bischoff
 General Manager

Zurich, 4.6.2013

Informácie o ochrane životného prostredia, zdravia a bezpečnosti (REACH)

Podrobné informácie ohľadom bezpečnosti a ochrany zdravia ako aj podrobné preventívne opatrenia, ako napr. fyzikálne, toxikologické a ekologické údaje sú uvedené v karte bezpečnostných údajov materiálu.

Právne oznámenia

Informácie, a najmä odporúčania, vzťahujúce sa na aplikáciu a konečné využitie Sika produktov sa podávajú v dobrej viere vyplývajúcej zo súčasných poznatkov a skúseností s výrobkami pri správnom skladovaní, manipulácii a aplikácii za normálnych podmienok v súlade s doporučeniami Sika.

V praxi rozdiely v materiáloch, substrátoch a v skutočných podmienkach na stavbe sú také, že nemôže byť poskytnutá žiadna záruka, čo sa týka predajnosti alebo vhodnosti a použiteľnosti pre určitý účel, ani žiadny záväzok vyplývajúci z akéhokoľvek právneho vzťahu. Nemôže byť vyvodený žiadny záväzok ani z tejto informácie, ani zo žiadnych písomných odporúčaní alebo poskytnutých rád. Spracovávateľ produktu musí overiť vhodnosť produktu pre plánované použitie a účel. Sika si vyhradzuje právo na zmenu vlastností jej produktov.

Vlastnícke práva tretích strán musia byť dodržané. Všetky objednávky sa akceptujú podliehajúc našim platným všeobecným a obchodným podmienkam. Užívatelia by sa mali vždy odvolávať na posledné vydanie miestnych produktových listov pre konkrétny výrobok.



EN 1504-4

08

0921

DECLARATION OF PERFORMANCE Sikadur®-31 CF Normal

02	04	02	03	001	0	000039	1001
----	----	----	----	-----	---	--------	------

1. Product Type:

Unique identification code of the product-type:

Sikadur®

2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

-31 CF Normal

Batch Number (refer to packaging)

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Structural bonding products for bonded mortar or concrete

Repair method (4.4)

Conforming to the Annex ZA Table ZA.1b

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Sikadur®

**Sika Schweiz AG
Tueffenwies 16
CH-8048 Zuerich
Switzerland**

5. Contact Address:

Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not relevant (see 4)

6. AVCP:

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 2+ (for uses in buildings and civil engineering works)

System 3 (for uses subject to reaction to fire regulations)

7. Notified body:

In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 1504-4, System 2+:

Notified factory production control certification body No. 0921 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control, 0921-CPR-2054.

EN 1504-4, System 3:

Notified testing laboratory MPA Dresden, no. 0767 performed under AVCP System Type 3 testing regarding fire behavior and issued testing report no. 2007-B-4394/08, and classification report no. 2007-B-4394/07.

Declaration of Performance

8. Notified body:

In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant (see 7)

9. Declared performance

Structural bonding product for bonded mortar or concrete for uses other than low performance requirements			
Essential characteristics	Performance	Standard	Harmonized Technical Specification
Bond/adhesion strength	Pass (concrete failure)	EN 12636	EN 1504-4: 2004
Shear strength	$\geq 6 \text{ N/mm}^2$	EN 12615	
Compressive strength	$\geq 30 \text{ N/mm}^2$	EN 12190	
Shrinkage / expansion	$\leq 0.1\%$	EN 12617	
Workability	60 min. at 20°C	EN ISO 9514	
Sensitivity to Water	Pass	EN 12615	
Modulus of elasticity	$\geq 2'000 \text{ N/mm}^2$	EN ISO 178	
Coefficient of thermal expansion	$\leq 100 * 10^{-6}$	EN 1770	
Glass transition temperature	$\geq 40^\circ\text{C}$	EN 12614	
Reaction to fire	Euroclass E	EN 13501-1	
Durability	Pass	EN 13733	
Dangerous substances	NPD	(comply with 5.4)	


10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Rahel Nägeli Ganz
Product Engineer



Roland Bischoff
General Manager

Zuerich, 04.06.2013

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



For Further Information:
Sika Schweiz AG
Tueffenwies 16
CH-8048 Zuerich
Switzerland

Phone +41 58 436 40 40
www.sika.ch