



EN 13493

05

1349

VYHLÁSENIE O PARAMETROCH

Sikaplan® WT 6200 – 20C

02	07	04	60	200	0	200000	1005
----	----	----	----	-----	---	--------	------

1. Typ výrobku:

Jedinečný identifikačný kód typu výrobku:

Sikaplan® WT 6200

2. Typ, číslo výrobnej dávky alebo sériové číslo, alebo akýkoľvek iný prvok umožňujúci identifikáciu stavebného výrobku, ako sa vyžaduje podľa článku 11 ods. 4:

WT 6200 - 20C

(číslo šarže – vid' údaj na balení)

3. Zamýšľané použitia alebo použitia stavebného výrobku, ktoré uvádza výrobca, v súlade s uplatniteľnou harmonizovanou technickou špecifikáciou:

Homogénna vodonepriepustná fólia na báze pružného polyolefinu (FPO-PE) podľa normy EN 13493

Izolácia skládok tuhého odpadu

4. Meno, registrované obchodné meno alebo registrovaná ochranná známka a kontaktná adresa výrobcu, ako sa vyžaduje podľa článku 11 ods. 5:

Sikaplan®

**Sika Supply Center AG
Industriestrasse 26
6060 Sarnen
Switzerland**

5. Kontaktná adresa:

V prípade potreby meno a kontaktná adresa splnomocneného zástupcu, ktorého splnomocnenie zahŕňa úlohy vymedzené v článku 12 ods. 2:

Nie je relevantné (vid' článok 4)

6. Systém alebo systémy posudzovania a overovania nemennosti parametrov stavebného výrobku, ako sa uvádzajú v prílohe V:

Systém 2+

7. Notifikovaná osoba (hEN):

V prípade vyhlásenia o parametroch týkajúceho sa stavebného výrobku, na ktorý sa vzťahuje harmonizovaná norma:

1349

Notifikovaná osoba č. 1349 vykonala počiatočnú inšpekciu výrobného závodu a systému riadenia výroby a vykonáva priebežný dohľad nad systémom riadenia výroby a posudzovanie a hodnotenie systému riadenia výroby. Notifikovaná osoba vydala certifikát o zhode systému riadenia výroby č. 017.

8. Notifikovaná osoba (ETA):

V prípade vyhlásenia o parametroch týkajúceho sa stavebného výrobku, na ktorý bolo vypracované európske technické posúdenie:

Nie je relevantné (viď článok 7)

9. Deklarované parametre

Podstatné vlastnosti	Parametre	Skúšobná metóda	Harmonizované technické špecifikácie
Pevnosť v ťahu pozdĺžna	14.5 (± 4.0) N / mm ²	ISO R 527 – 1/3/5	EN 13493: 2005
Pevnosť v ťahu priečna	10.0 (± 4.0) N / mm ²	ISO R 527 – 1/3/5	
Odolnosť proti statickému zaťaženiu	3.00 (± 0.35) kN	EN ISO 12236	
Vodotesnosť	< 10 ⁻⁷ m ³ x m ⁻² x d ⁻¹	EN 14150:2001	
Plynotesnosť	< 10 ⁻⁷ m ³ x m ⁻² x d ⁻¹	ASTM D 1434	
Odolnosť proti poveternostným vplyvom	Ostávajúca pevnosť v ťahu a predĺženie : ≥ 75 %	EN 12224 (350 MJ/m ²) ISO 527-3/5/100	
Odolnosť proti oxidácii	Zmena pevnosti v ťahu a predĺženie: ≤ 10 %	EN 14575 (90d / 85°C); ISO 527-3/5	
Praskanie vplyvom environmentálneho napätia	≥ 200 h	ASTM D 5397-99 (EN 14576)	

10. Deklarácia

Parametre výrobku uvedené v bodoch 1 a 2 sú v zhode s deklarovateľnými parametrami v bode 9. Toto vyhlásenie o parametroch sa vydáva na výhradnú zodpovednosť výrobcu uvedeného v bode 4.

Podpísal(-a) za a v mene výrobcu:

nečitateľný podpis
 Hans-Jörg Stich
 Corporate Product Engineer

nečitateľný podpis
 Marcel Langenegger
 CMFM Waterproofing

Sarnen, 13.2.2013

Informácie o ochrane životného prostredia, zdravia a bezpečnosti

Pre tento produkt nie je potrebné vypracovať kartu bezpečnostných údajov podľa nariadenia ES č. 1907/2006, článok 31 pri uvádzaní produktu na trh, preprave alebo použití. Produkt nepoškodzuje životné prostredie pri uvedenom použití.

REACH

Nariadenie Európskeho parlamentu a Rady (ES) č. 1907/2006 o registrácii, hodnotení, autorizácii a obmedzovaní chemických látok (REACH)

Tento produkt je výrobok v zmysle článku č. 3 Nariadenia ES č. 1907/2006 (REACH). Neobsahuje žiadne látky, ktoré by sa mohli uvoľniť z výrobku pri bežných alebo odôvodnene predpokladaných podmienkach použitia. Pre tento produkt nie je potrebné vypracovať kartu bezpečnostných údajov podľa článku 31 toho istého nariadenia pri uvádzaní produktu na trh, preprave alebo použití. Pre bezpečné používanie dodržiavajte príslušný produktový list.

Na základe našich aktuálnych vedomostí tento produkt neobsahuje SVHC látky (látky vzbudzujúce veľmi veľké obavy) z kandidátskeho zoznamu publikovaného Európskou chemickou agentúrou v koncentrácii viac ako 0,1 % (w/w).

Právne oznámenia

Informácie, a najmä odporúčania, vzťahujúce sa na aplikáciu a konečné využitie Sika produktov sa podávajú v dobrej viere vyplývajúcej zo súčasných poznatkov a skúseností s výrobkami pri správnom skladovaní, manipulácii a aplikácii za normálnych podmienok v súlade s doporučeniami Sika.

V praxi rozdiely v materiáloch, substrátoch a v skutočných podmienkach na stavbe sú také, že nemôže byť poskytnutá žiadna záruka, čo sa týka predajnosti alebo vhodnosti a použiteľnosti pre určitý účel, ani žiadny záväzok vyplývajúci z akéhokoľvek právneho vzťahu. Nemôže byť vyvozený žiadny záväzok ani z tejto informácie, ani zo žiadnych písomných odporúčaní alebo poskytnutých rád. Spracovávateľ produktu musí overiť vhodnosť produktu pre plánované použitie a účel. Sika si vyhradzuje právo na zmenu vlastností jej produktov.

Vlastnícke práva tretích strán musia byť dodržané. Všetky objednávky sa akceptujú podliehajú našim platným všeobecným a obchodným podmienkam. Užívatelia by sa mali vždy odvolávať na posledné vydanie miestnych produktových listov pre konkrétny výrobok.



EN 13493

05

1349

DECLARATION OF PERFORMANCE Sikaplan® WT 6200 – 20C

02	07	04	60	200	0	200000	1005
----	----	----	----	-----	---	--------	------

1. Product Type:

Unique identification code of the product-type:

Sikaplan® WT 6200

2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

WT 6200 – 20C (lot nr. see packaging)

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Sheet waterproofing membrane with an inlay for restraint, based on flexible polyolefin (FPO-PE) to EN 13493

Lining of solid waste deposits

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Sikaplan®

**Sika Supply Center AG
Industriestrasse 26
6060 Sarnen
Switzerland**

5. Contact Address:

Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not relevant (see 4)

6. AVCP:

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 2+

7. Notified body:

In case of the declaration of performance concerning a construction product covered by a harmonised standard:

1349

Notified factory production control certification body No. 1349 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control (FPC) 017.

Declaration of Performance



8. Notified body:

In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant (see 7)

9. Declared performance

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Tensile Strength machine direction	14.5 (± 4.0) N / mm ²	ISO R 527 – 1/3/5	EN 13493: 2005
Tensile Strength cross direction	10.0 (± 4.0) N / mm ²	ISO R 527 – 1/3/5	
Resistance to static puncture	3.00 (± 0.35) kN	EN ISO 12236	
Liquid tightness	< 10 ⁻⁷ m ³ x m ⁻² x d ⁻¹	EN 14150:2001	
Gas tightness	< 10 ⁻⁷ m ³ x m ⁻² x d ⁻¹	ASTM D 1434	
Durability weathering	Remaining tensile strength and elongation: ≥ 75 %	EN 12224 (350 MJ/m ²) ISO 527-3/5/100	
Durability oxidation	Change of tensile strength and elongation: ≤ 10 %	EN 14575 (90d / 85 °C); ISO 527-3/5	
Durability environmental stress cracking	≥ 200 h	ASTM D 5397-99 (EN 14576)	



10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Hans-Jörg Stich
 Corporate Product Engineer



Marcel Langenegger
 CMFM Waterproofing

Sarnen, 13 February 2013

Ecology, Health and Safety Information

This product is an article within the meaning of Article 3.3 of Regulation (EC) No. 1907/2006. A safety data sheet following EC- Regulation 1907/2006, article 31 is not needed to bring the product to the market to transport or use it. The product does not damage the environment when used as specified.

REACH

**European Community Regulation on chemicals and their safe use
 (REACH: EC 1907/2006)**

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet.

Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation, or on the candidate list published by the European Chemicals Agency in concentrations above 0.1% (w/w).

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



For Further Information:
 Sika Services AG
 CMFM Waterproofing
 Industriestrasse 26
 6060 Sarnen
 Switzerland

Phone +41 58 436 76 37
 Telefax +41 58 436 78 83
 www.sika.com